

Kits for 6 panels with 30mm clamps with Grounding Pins

Component

					
ER-I-05A/EZC/ECO 12 Units	ER-IC-ST30/G 10 Units	ER-EC-ST30 4 Units	EZ-CC-PV/2 12 Units	EZ-GL-AT 2 Units	ER-SP-ELT 2 Units
Tin ezClick Kit with Elite-Rails for 6 panels with 30mm clamps with Grounding Pins Part No.: K-SR-05/EZC/6/30/G (bar code: 21-136-00081)					

					
ER-I-01/EZC/ECO 12 Units	ER-IC-ST30/G 10 Units	ER-EC-ST30 4 Units	EZ-CC-PV/2 12 Units	EZ-GL-AT 2 Units	ER-SP-ELT 2 Units
Tile ezClick Kit with Elite-Rails for 6 panels with 30mm clamps with Grounding Pins Part No.: K-SR-01/EZC/6/30/G (bar code: 21-137-00068)					

Technical Specification

Application	K-SR-05/EZC/6/30/G: Tin Roof K-SR-01/EZC/6/30/G : Tile Roof
Purlin Requirement	K-SR-05/EZC/6/30/G: Metal or Timber purlin K-SR-01/EZC/6/30/G : Timber purlin
Screw Specification	K-SR-05/EZC/6/30/G: Buildex 14-11 x 70 (14 gauge, 6.3 mm, 11 TPI, 70 mm long) Hex Head Zips Screw K-SR-01/EZC/6/30/G : Buildex 14-10 x 65 (14 gauge, 6.3 mm, 10 TPI, 65 mm long) Hex Head Zips Screw
PV panel dimension	Framed PV Modules of 30 mm in height
Weight	K-SR-05/EZC/6/30/G: 3.087 Kg K-SR-01/EZC/6/30/G : 8.979 Kg
Packaging	K-SR-05/EZC/6/30/G: 1 unit per pack; 4 packs (4 units) per carton K-SR-01/EZC/6/30/G : 1 unit per pack; 2 packs (2 units) per carton
Material	Tin Interface: AL6005-T5 Tile Interface: SUS304 Cable Clip: SUS304(3/4H) Grounding Lug: SUS316 & AL6005-T5 Clamp and Splice: AL6005-T5
Standard	AS NZS1170.2-2021