







Rotary Actuator Switch - Lockable Off



- Rotary Actuator Switch
- Lockable Off
- Panel Mounting, IP66
- Rotary Handle 64mm²
- IP40 Body
- NEMA Type 3R



Data according to IEC 60947-3, VDE 0660

DC21B Rating							Poles in series	Number of Strings	Weight kg/pcs.	Part Number	Contact Configuration
600V	700V	800V	900V	1000V	1200V	1500V					
16A	16A	16A	13A	9A	6A	3A	2	1	0.21	SI16 PM64R 2	
25A	23A	20A	16A	11A	8A	4A	2	1	0.21	SI25 PM64R 2	
32A	27A	23A	20A	13A	10A	5A	2	1	0.21	SI32 PM64R 2	
29A	16A	16A	13A	9A	6A	3A	2	1	0.26	SI16 PM64R 2H	
45A	23A	20A	16A	11A	8A	4A	2	1	0.26	SI25 PM64R 2H	
50A	27A	23A	20A	13A	10A	5A	2	1	0.26	SI32 PM64R 2H	
16A	16A	16A	13A	9A	6A	3A	2	2	0.24	SI16 PM64R 4	
25A	23A	20A	16A	11A	8A	4A	2	2	0.24	SI25 PM64R 4	
32A	27A	23A	20A	13A	10A	5A	2	2	0.24	SI32 PM64R 4	
16A	16A	16A	16A	16A	16A	16A	4	1	0.25	SI16 PM64R 4S	
25A	25A	25A	25A	25A	25A	20A	4	1	0.25	SI25 PM64R 4S	
32A	32A	32A	32A	32A	32A	23A	4	1	0.25	SI32 PM64R 4S	
16A	16A	16A	16A	16A	16A	16A	4	1	0.25	SI16 PM64R 4T	
25A	25A	25A	25A	25A	25A	20A	4	1	0.25	SI25 PM64R 4T	
32A	32A	32A	32A	32A	32A	23A	4	1	0.25	SI32 PM64R 4T	
16A	16A	16A	16A	16A	16A	16A	4	1	0.25	SI16 PM64R 4B	
25A	25A	25A	25A	25A	25A	20A	4	1	0.25	SI25 PM64R 4B	
32A	32A	32A	32A	32A	32A	23A	4	1	0.25	SI32 PM64R 4B	
16A	16A	16A	13A	9A	6A	3A	2	3	0.37	SI16 PM64R 6	
25A	23A	20A	16A	11A	8A	4A	2	3	0.37	SI25 PM64R 6	
32A	27A	23A	20A	13A	10A	5A	2	3	0.37	SI32 PM64R 6	
16A	16A	16A	13A	9A	6A	3A	2	4	0.42	SI16 PM64R 8	
25A	23A	20A	16A	11A	8A	4A	2	4	0.42	SI25 PM64R 8	
32A	27A	23A	20A	13A	10A	5A	2	4	0.42	SI32 PM64R 8	
29A	29A	29A	29A	29A	29A	16A	8	1	0.47	SI16 PM64R 4H	
45A	45A	45A	45A	45A	45A	20A	8	1	0.47	SI25 PM64R 4H	
58A	58A	58A	58A	58A	50A	23A	8	1	0.47	SI32 PM64R 4H	

Extended Switch Shaft for all switches for panel mounting: Type Suffix

x= panel thickness

+ "x"