

Address: PO BOX 4321, PALMERSTON, NT 0831
ABN: 44 600 817 463

Mob: 0402 123 891
Email: admin@albright.net.au

**WIND PRESSURE TESTING OF TW SOLAR PANEL MODELS:
TWMNH-48HDXXX; TWMNH-48HEXXX & TWMNH-48HWXXX (SOLAR PHOTOVOLTAIC
MODULES)**

ACE REFERENCE: ACE 25-161.01, REV: 02

Date of Issue: 30th of July 2025

Tongwei Co., Ltd.

Attention: Mr Leon Hu

Mob: +86 028-60707985

Email: HUL038@tongwei.com

Address: No. 588, Middle Section Tianfu Avenue, High-Tech Zone, Chengdu, China (Sichuan) Pilot Free Trade Zone

RE: TW Solar Panel Modules: 1762 mm x 1134 mm x 30 mm, 22.8 kg, Models: TWMNH-48HD440, TWMNH-48HD445, TWMNH-48HD450, TWMNH-48HD455, TWMNH-48HD460 & TWMNH-48HD465, TWMNH-48HE440, TWMNH-48HE445, TWMNH-48HE450, TWMNH-48HE455, TWMNH-48HE460, TWMNH-48HE465, TWMNH-48HE470, TWMNH-48HW440, TWMNH-48HW445, TWMNH-48HW450, TWMNH-48HW455, TWMNH-48HW460, TWMNH-48HW465, TWMNH-48HW470 & TWMNH-48HW475 with 2 Supports at 800 mm & 2 Supports at 1200 mm Centres

This Test Report certifies the Recommended Design Wind Pressure(s) for the above-mentioned TW Solar Panels, Models: TWMNH-48HDXXX, 1762 mm x 1134 mm x 30 mm, 22.8 kg, TWMNH-48HEXXX, 1762 mm x 1134 mm x 30 mm, 22.8 kg & TWMNH-48HWXXX, 1762 mm x 1134 mm x 30 mm, 22.8 kg. This Test Report is for the testing of the PV Module Frames only, and does not cover the supporting elements/ rails and or associated fixings of the tested panels to the supporting elements/ rails.

This Report verifies that the PV Modules are capable of withstanding the Design Wind Loads when installed to an approved railing system with the corresponding support points as listed in Table 1.

The same Recommended Ultimate Capacities determined for the test of TWMNH-48HD445 within this report, may also be applied to the specified models: TWMNH-48HEXXX & TWMNH-48HWXXX.

The Manufacturer has provided a Declaration Letter (Dated: 3/07/2025) stating that all three models: TWMNH-48HDXXX, TWMNH-48HEXXX & TWMNH-48HWXXX, are both mechanically & physically identical and are both manufactured in the exact same way with the exact same materials. Refer to Declaration Letter attached in Appendix Section.

Albright Consulting Engineers (ACE) Pty Ltd were engaged by Tongwei Co., Ltd. to carry out and witness 6 individual mechanical load tests (simulated static, wind load strength test). The testing was performed on new panels supplied by Tongwei Co., Ltd.

Address: PO BOX 4321, PALMERSTON, NT 0831
ABN: 44 600 817 463

Mob: 0402 123 891
Email: admin@albright.net.au

A total of 6 individual panels were tested (**TWMNH-48HD445**). The following tests were carried out:

- Test Scope 1: 3 individual test samples with 2 supports/ clamps at 800 mm centres;
- Test Scope 2: 3 individual test samples with 2 supports/ clamps at 1200 mm centres;

The solar panel module(s) were mounted front side up using fixing clamps and brackets, which are then bolted to the test bed chassis. This is was to imitate a real-world situation; (this process was repeated for each test sample).

A constant pressure/ load was applied by an airbag located the back of the panel. A calibrated digital manometer was used to measure and track the design test pressures, while a calibrated digital deflection meter was used to measure and record the centre (vertical) deflection of the solar panel at 1kPa intervals. The electrical continuity or the cells themselves were not monitored during each of the tests.

Note that a mechanical load testing and or simulated static, wind load strength testing was carried out for the above-mentioned solar panel module samples and the support fixing configuration(s). The testing procedure that was adopted is generally accordance to the methods outlined in AS4040 (series), Static Strength Test Regime.

The 6 individual simulated static, wind load strength tests were conducted and observed by Nicholas Kastellorizios a representative of Albright Consulting Engineers in Darwin Northern Territory, on the 20th June 2025. The behaviour of the modules was observed and recorded.

Material Variability Factor AS/NZS 1170.0, Table B1 – kt:

The applied factor for variability for 1 individual test sample (1 individual units tested per support centre) and adopting a coefficient of variation of structural characteristics of 10% in accordance with AS/NZS 1170.0, Table B1 (when determining the allowable design capacity) is 1.46.

The applied factor for variability for 2 individual test samples (2 individual units tested per support centre) and adopting a coefficient of variation of structural characteristics of 10% in accordance with AS/NZS 1170.0, Table B1 (when determining the allowable design capacity) is 1.38.

The applied factor for variability for 3 individual test samples (3 individual units tested per support centre) and adopting a coefficient of variation of structural characteristics of 10% in accordance with AS/NZS 1170.0, Table B1 (when determining the allowable design capacity) is 1.33.

Address: PO BOX 4321, PALMERSTON, NT 0831
ABN: 44 600 817 463

Mob: 0402 123 891
Email: admin@albright.net.au

Results & Observations:

Test No.1, x3 Samples, TW Solar Panel Modules: TWMNH-48HD445, 1762 mm x 1134 mm x 30 mm, 22.8 kg, with 2 Supports at 800 mm Centres. Serial Numbers: N3E253002000026, N3E253002000020 & N3E253002000012

The above-mentioned solar panel samples were mounted to the test rig with 2 supports at **800 mm** centres apart on each side with a cantilever/ overhang of approximately **481 mm** at each end.

During all three individual tests, the solar panel modules were observed to be able to support an equivalent design test pressure of **6.5 kPa**, with a centre vertical deflection **77 mm** (approximately).

It was observed that during each test, as the test pressures were increased, the top flanges of longer rail framing elements appeared to roll inwards. This rolling or torsional effect caused concentrated pressures/ stress to form along the top (glass) face of the panel. This was more evident at the clamping zones of the panel, as localised indentations to the top face of solar panel modules were observed in each case.

It was also observed during all three tests, while increasing the design test pressure the solar panel modules buckled upwards, causing the shorter rail elements to curve/ buckle upwards in an arch like manner. If increased further, this would have likely caused the panel(s) pop out from the fixing clamps and or either cause the frame to fail, resulting in the failure of the glass front face.

This was evident, as during one test case, when the test pressures were increased beyond 6.5 kPa, this caused one of the solar panel modules to shatter or fail.

The top flanges of the rails had experienced minor crushing caused by high bearing stresses caused by the fixing clamps while the frame was under test pressures. This was exacerbated when the test pressures were increased.

During the testing scope, the glass front face of the solar panel modules did not appear to shatter or crack (only during the one case). There were visually obvious signs of minor structural fatigue occurring at the shorter framing elements of the solar panel modules that did not fail. Indicating that the plastic limit of the material may have been reached.

In all three cases, after the test pressure was released, there was a very slight permanent deflection of approximately 5 mm to 10 mm observed at the centre of shorter framing elements. This indicated that the frames had started to yield/ entered the plastic phase of the material. However, no failure was recorded and the panels remained in the fixing clamps.

The internal rails located at the underside of the panel also were buckled with a permanent deflection between 5 to 10mm, indicating that the elements had yielded.

(Note there were very consistent results and observations during all three tests)

Address: PO BOX 4321, PALMERSTON, NT 0831
ABN: 44 600 817 463

Mob: 0402 123 891
Email: admin@albright.net.au

Results & Observations:

Test No.2, x3 Samples, TW Solar Panel Modules: TWMNH-48HD445, 1762 mm x 1134 mm x 30 mm, 22.8 kg, with 2 Supports at 1200 mm Centres. Serial Numbers: N3E253002000023, N3E253002000027 & N3E253002000028

The above-mentioned solar panel samples were mounted to the test rig with 2 supports at **1200 mm** centres apart on each side with a cantilever/ overhang of approximately **281 mm** at each end.

During all three individual tests, the solar panel modules were observed to be able to support an equivalent design test pressure of **6.5 kPa**, with a centre vertical deflection **78.5 mm** (approximately).

It was observed that during each test, as the test pressures were increased, the top flanges of longer rail framing elements appeared to roll inwards. This rolling or torsional effect caused concentrated pressures/ stress to form along the top (glass) face of the panel. This was more evident at the clamping zones of the panel, as localised indentations to the top face of solar panel modules were observed in each case.

It was also observed during all three tests, while increasing the design test pressure the solar panel modules buckled upwards, causing the shorter rail elements to curve/ buckle upwards in an arch like manner. If increased further, this would have likely caused the panel(s) pop out from the fixing clamps and or either cause the frame to fail, resulting in the failure of the glass front face.

This was evident, as during one test case, when the test pressures were increased beyond 6.5 kPa, this caused one of the solar panel modules to shatter or fail.

The top flanges of the rails had experienced minor crushing caused by high bearing stresses caused by the fixing clamps while the frame was under test pressures. This was exacerbated when the test pressures were increased.

During the testing scope, the glass front face of the solar panel modules did not appear to shatter or crack (only during the one case). There were visually obvious signs of minor structural fatigue occurring at the shorter framing elements of the solar panel modules that did not fail. Indicating that the plastic limit of the material may have been reached.

In all three cases, after the test pressure was released, there was a very slight permanent deflection of approximately 5 mm to 10 mm observed at the centre of shorter framing elements. This indicated that the frames had started to yield/ entered the plastic phase of the material. However, no failure was recorded and the panels remained in the fixing clamps.

The internal rails located at the underside of the panel also were buckled with a permanent deflection between 5 to 10mm, indicating that the elements had yielded.

(Note there were very consistent results and observations during all three tests)

Address: PO BOX 4321, PALMERSTON, NT 0831
ABN: 44 600 817 463

Mob: 0402 123 891
Email: admin@albright.net.au

Other Observations:

In our opinion the changes to the physical geometry of the solar panel modules is a major contributing factor to the overall failure and performance of the panel, i.e., the grade of aluminium; the depth of the frame being 30 mm, as well as the length of the shorter rails being wider at 1134 mm.

The reductions in capacities when compared to other models tested previously are likely due to the overall system not being as stiff or robust as previous models. Previous models had deeper framing elements with 40mm to 45mm thicker framing and glass elements, with wider flanges to all framing elements, and were also narrower (approx. 990mm), which provided an overall stiffer system, giving them the ability to resist these concentrated localised pressures at the clamping zones, as well as at the corners of the frame.

Other likely factors that may have contributed to the failure or affected performance of these panels include:

1. Thickness & Grade of Glass Face;
2. Thickness of Backing Material;
3. Material used for Backing Material, dual layer glass solar panels appear to be less flexible than solar panels with PET (polyester) or fluoropolymers (PVF, PVDF, PTFE) backing materials;
4. Grade of Aluminium used in the manufacturer of the Frame;
5. Alternative framing elements, some rails do not have flanges, only a thin narrow box sections;
6. Inner Frame Connections/ Junctions;
7. Glass Supports within Frame;
8. Lack of and or quality of Adhesive of between the rails & Sheeting Layers.
9. Packing. Transport and Handling of Samples.

Table 1: Test Summary: Recommended Ultimate Design Strength, Limit Design Capacity

Test	Panel Manufacturer, Model & Size (mm)	Support Centres (mm)	Maximum Applied Load (kPa)	Material Variability Factor AS/NZS 1170.0 Table B1 – kt	Recommended Ultimate Design Strength Limit State Design Capacity (kPa)
No.1	X3 Samples: TW Solar Panel Modules: TWMNH-48HD445, 1762 mm x 1134 mm x 30 mm, 22.8 kg	2 Supports at 800mm	6.5	1.33	4.89
No.2	X3 Samples: TW Solar Panel Modules: TWMNH-48HD445, 1762 mm x 1134 mm x 30 mm, 22.8 kg	2 Supports at 1200mm	6.5	1.33	4.89

Note that the above mentioned Recommended Ultimate Design Strength, Limit Design Capacities are only applicable to the models & power series stated within this certificate, as well as listed on the attached data sheet(s).

Note that the Project Engineer/ Design Engineer should consider the panel deflection as a design criteria. These deflections could cause the panels to pop/ slip out of the fixing clamps.

Address: PO BOX 4321, PALMERSTON, NT 0831
 ABN: 44 600 817 463

Mob: 0402 123 891
 Email: admin@albright.net.au

TW Solar Panel Modules, TWMNH-48HDXXX, Mechanical Properties:

Cell Type:	TCN (N Type Monocrystalline Cell)
Cells:	96(6x16)
Dimensions:	1762 mm x 1134 mm x 30 mm
Weight:	22.8 kg
Front Material/ Superstrate:	2.0 mm AR Coating Semi Tempered Glass
Backing Material/ Substrate:	2.0 mm Semi Tempered Glass (Transparent)
Frame:	30 mm Anodized Aluminium Alloy Black Frame

TW Solar Panel Modules, TWMNH-48HEXXX, Mechanical Properties:

Cell Type:	TCN (N Type Monocrystalline Cell)
Cells:	96(6x16)
Dimensions:	1762 mm x 1134 mm x 30 mm
Weight:	22.8 kg
Front Material/ Superstrate:	2.0 mm AR Coating Semi Tempered Glass
Backing Material/ Substrate:	2.0 mm Semi Tempered Glass (Transparent)
Frame:	30 mm Anodized Aluminium Alloy Black Frame

TW Solar Panel Modules, TWMNH-48HWXXX, Mechanical Properties:

Cell Type:	TCN (N Type Monocrystalline Cell)
Cells:	96(6x16)
Dimensions:	1762 mm x 1134 mm x 30 mm
Weight:	22.8 kg
Front Material/ Superstrate:	2.0 mm AR Coating Semi Tempered Glass
Backing Material/ Substrate:	2.0 mm Semi Tempered Glass (Transparent)
Frame:	30 mm Anodized Aluminium Alloy Black Frame

Refer to the attached Declaration Letter (Dated: 3/07/2025) stating that all three models: TWMNH-48HDXXX, TWMNH-48HEXXX & TWMNH-48HWXXX, are both mechanically & physically identical and are both manufactured in the exact same way with the exact same materials. Refer to Declaration Letter attached in Appendix Section.

Address: PO BOX 4321, PALMERSTON, NT 0831
ABN: 44 600 817 463

Mob: 0402 123 891
Email: admin@albright.net.au

Summary:

We recommended and verify that the **TW Solar Panel Modules, Models: TWMNH-48HD440, TWMNH-48HD445, TWMNH-48HD450, TWMNH-48HD455, TWMNH-48HD460 & TWMNH-48HD465, TWMNH-48HE440, TWMNH-48HE445, TWMNH-48HE450, TWMNH-48HE455, TWMNH-48HE460, TWMNH-48HE465, TWMNH-48HE470, TWMNH-48HW440, TWMNH-48HW445, TWMNH-48HW450, TWMNH-48HW455, TWMNH-48HW460, TWMNH-48HW465, TWMNH-48HW470 & TWMNH-48HW475, (1762 mm x 1134 mm x 30 mm, 22.8 kg)**; Solar Panel Modules can resist the following vertical design loads, with a Recommended Ultimate Design Strength (Limit State Design Capacity), as listed for the following support conditions:

- **Supported on purlins/ battens, 2 supports/ rails at 800 mm centres: 4.89 kPa;**
- **Supported on purlins/ battens, 2 supports/ rails at 1200 mm centres: 4.89 kPa;**

This Report has been prepared on behalf of and for the exclusive use of Tongwei Co., Ltd. and is for the testing of the PV Module Frame only; and **not** the supporting elements, clamps, rails and or associated fixings of the PV Modules to the rails.

The Recommended Ultimate Design Strength, Limit State Design Capacities, (kPa) are only applicable for the panel model; size, weight and support/ rail spacing's as the above-mentioned tested model(s). Any additional power output models referenced may also be covered under this certificate provided that they are referenced in the same technical datasheet (attached); are mechanically & physically identical to the (tested): **TW Solar Panel Modules: TWMNH-48HD445, 1762 mm x 1134 mm x 30 mm, 22.8 kg**; and that they are manufactured in the exact same way with the exact same materials as the (tested): **TW Solar Panel Modules: TWMNH-48HD445, 1762 mm x 1134 mm x 30 mm, 22.8 kg**. Refer to Appendix A for datasheet.

The same Recommended Ultimate Capacities determined for the test of TWMNH-48HD445 within this report, may also be applied to the specified models: TWMNH-48HEXXX & TWMNH-48HWXXX.

The Manufacturer has provided a Declaration Letter (Dated: 3/07/2025) stating that all three models: TWMNH-48HDXXX, TWMNH-48HEXXX & TWMNH-48HWXXX, are both mechanically & physically identical and are both manufactured in the exact same way with the exact same materials. Refer to Declaration Letter attached in Appendix Section.

Address: PO BOX 4321, PALMERSTON, NT 0831
ABN: 44 600 817 463

Mob: 0402 123 891
Email: admin@albright.net.au

This certificate and certification is no longer valid if:

1. If any of the Engineering & Mechanical Properties used in the manufacture of the solar panel modules/ models is altered or changed in any way to the above mentioned tested solar panel modules/ models.
2. If any of the manufacturing processes or techniques used in the manufacture of the solar panel modules/ models is altered or changed in any way to the above mentioned tested solar panel modules/ models.
3. It is the responsibility of the manufacturer to confirm if there has been any alterations, changes or revisions to the physical makeup of the frame, i.e. aluminium grade, front glass face or backing sheet, etc.; or if the manufacturing process has altered or changed in any way, re-testing may be required.
4. This certificate is rendered invalid if any changes have occurred to the tested modules/ models as noted above.

Important Notes:

1. Note that the deflection criteria of the panels themselves may govern or limit the structural design and should be considered in high design wind pressure zones; as excessive deflections may cause the panel's to slip and or pop out from the fixing clamps.
2. The panel fixing clamps; the support rails; their associated fixings or the fixings of the L Feet to the immediate supporting structure, were not tested as part of the test procedure/ scope, and therefore no comment can be made as to their role as a potential failure mode. Note that these elements must be individually evaluated and confirmed by the Project Engineer and or the Design Engineer, as they may limit the structural design or capacity of the total structural system.
3. The railing system is excluded from this certification and is designed & certified by others.
4. The immediate supporting elements for the PV Roof Mounted Solar Panel System is also excluded from this certification and is designed & certified by others.
5. This Report verifies the Design Wind Pressures for the above referenced Solar Panel Modules/ Modes. However, they are subject to the analysis and approval by the Project Engineer; Design Engineer and or Approved Competent Person on a project by project basis. Note that the Design Engineer must confirm that the Design Wind Pressures are less than the Recommend Capacities referenced within this report, for each specific project.

Company Name if certification issued on behalf of a corporation Albright Services Group Pty Ltd, Trading as Albright Consulting Engineers		Company NT Registration Number 215037ES	
I certify that reasonable care has been taken to ensure that the structural engineering aspects of the works as described above have been designed in accordance with the requirements of the Building Code of Australia and the Northern Territory Building Regulations			
Name Nicholas Kastellorizios Nominee for Albright Services Group Pty Ltd, Trading as Albright Consulting Engineers	Nominee/Individual NT Registration Number 215037ES	Signature 	Date 30/07/2025

Please contact our office if you require any further information in relation to this report.

Nicholas Kastellorizios
Director/ Structural Engineer
Albright Consulting Engineers



Address: PO BOX 4321, PALMERSTON, NT 0831
ABN: 44 600 817 463

Mob: 0402 123 891
Email: admin@albright.net.au

Appendix:

Data Sheet: TW Solar Panel Modules, Models: TWMNH-48HD440, TWMNH-48HD445, TWMNH-48HD450, TWMNH-48HD455, TWMNH-48HD460 & TWMNH-48HD465, TWMNH-48HE440, TWMNH-48HE445, TWMNH-48HE450, TWMNH-48HE455, TWMNH-48HE460, TWMNH-48HE465, TWMNH-48HE470, TWMNH-48HW440, TWMNH-48HW445, TWMNH-48HW450, TWMNH-48HW455, TWMNH-48HW460, TWMNH-48HW465, TWMNH-48HW470 & TWMNH-48HW475, (1762 mm x 1134 mm x 30 mm, 22.8 kg);

Declaration Letter, issued by Tongwei Co., Ltd.

Declaration letter

To ALBRIGHT,

We (Tongwei Co., Ltd., address: No. 588, Middle Section Tianfu Avenue, High-Tech Zone, Chengdu, China (Sichuan) Pilot Free Trade Zone) hereby declare that the TWMNH-48HDxxx, TWMNH-48HExxx and TWMNH-48HWxxx, PV modules are made up of glass, encapsulation material, frame, adhesive and other materials, all models are mechanically & physically identical to each other and manufactured in the exact same way with the exact same materials as each other, details for these main physical support materials are shown in the table below. The mechanical properties of the main materials (e.g. the front/rear glass, encapsulation material, frame and adhesive) used in PV modules are identical, please find the details in the datasheet below.

Hereby declare!

Best regards!



Leon Hu 2025.7.3

No.	Material	Manufacturer	Technical data for TWMNH-48HDxxx	Technical data for TWMNH-48HExxx	Technical data for TWMNH-48HWxxx
1	Front glass	Tongwei Solar (Hefei) Co., Ltd.	Material: AR coating semi tempered glass Thickness=2.0±10%mm	Material: AR coating semi tempered glass Thickness=2.0±10%mm	Material: AR coating semi tempered glass Thickness=2.0±10%mm
2	Encapsulation material (front)	Tongwei Solar (Hefei) Co., Ltd.	Material: EPE Type: TWPET01 Thickness=0.55±0.11mm	Material: EPE Type: TWPET01 Thickness=0.55±0.11mm	Material: EPE Type: TWPET01 Thickness=0.55±0.11mm
3	Encapsulation material (rear)	Tongwei Solar (Hefei) Co., Ltd.	Material: EVA Type: TWET01 Thickness=0.55±0.11mm Color: Transparent	Material: EVA Type: TWEB01 Thickness=0.55±0.11mm Color: Black	Material: EVA Type: TWEW01 Thickness=0.55±0.11mm Color: White
4	Rear glass	Tongwei Solar (Hefei) Co., Ltd.	Material: semi tempered glass Thickness=2.0±10%mm Color: transparent	Material: semi tempered glass Thickness=2.0±10%mm Color: transparent	Material: semi tempered glass Thickness=2.0±10%mm Color: transparent
5	Frame	Tongwei Solar (Hefei) Co., Ltd.	Material: Anodized aluminum alloy Grade: 6005-T6 Thickness=30mm Color: Black	Material: Anodized aluminum alloy Grade: 6005-T6 Thickness=30mm Color: Black	Material: Anodized aluminum alloy Grade: 6005-T6 Thickness=30mm Color: Black
6	Adhesive	Jiangsu Tianchen New Materials Co., Ltd.	Material: Silicone Type/Grade: HT-8258 Color: White	Material: Silicone Type/Grade: HT-8258 Color: Black	Material: Silicone Type/Grade: HT-8258 Color: White

Leon Hu 2025.7.3



High Power Output
Low LCOE



Maximum Power
465W



TWMNH

N-type Half-cell
Bifacial Black Frame Module (48)

48HD440-465W




TIER 1
Bloomberg
NEW ENERGY FINANCE

Tongwei Co., Ltd.
<https://en.tongwei.cn/>



Learn More

Drawings (Unit: mm)



Electrical characteristics (STC)

Module type:	TWMNH-48 HD440	TWMNH-48 HD445	TWMNH-48 HD450	TWMNH-48 HD455	TWMNH-48 HD460	TWMNH-48 HD465
Maximum Power: P _{max} [W]	440	445	450	455	460	465
Open Circuit Voltage: V _{oc} [V]	35.35	35.55	35.75	35.95	36.15	36.35
Short Circuit Current: I _{sc} [A]	15.89	15.92	15.95	15.98	16.05	16.12
Voltage at Maximum Power: V _{mp} [V]	29.67	29.93	30.19	30.44	30.69	30.94
Current at Maximum Power: I _{mp} [A]	14.83	14.87	14.91	14.95	14.99	15.03
Module Efficiency: η [%]	22.0	22.3	22.5	22.8	23.0	23.3

* STC: Irradiance 1000W/m², Cell Temperature 25°C, AM=1.5, Power measurement tolerance: ±3%

Electrical characteristics (BNPI)

Maximum Power: P _{max} [W]	485.7	491.5	496.9	502.3	507.9	513.3
Open Circuit Voltage: V _{oc} [V]	35.35	35.55	35.75	35.95	36.15	36.35
Short Circuit Current: I _{sc} [A]	17.54	17.57	17.61	17.64	17.72	17.80
Voltage at Maximum Power: V _{mp} [V]	29.67	29.93	30.19	30.44	30.69	30.94
Current at Maximum Power: I _{mp} [A]	16.37	16.42	16.46	16.50	16.55	16.59

* BNPI: Front side irradiance 1000W/m², Rear side irradiance 135W/m², Cell Temperature=25°C, AM=1.5, Power measurement tolerance: ±3%

Electrical characteristics with different rear side power gain

Maximum Power: P _{max} [W]	462	467	472	477	483	488
Module Efficiency: η [%]	23.1	23.4	23.6	23.9	24.2	24.4
Maximum Power: P _{max} [W]	506	511	517	523	529	534
Module Efficiency: η [%]	25.3	25.6	25.9	26.2	26.5	26.7
Maximum Power: P _{max} [W]	550	556	562	568	575	581
Module Efficiency: η [%]	27.5	27.8	28.1	28.4	28.8	29.1

Temperature rating

Temperature Coefficient of P _{max}	-0.28%/°C
Temperature Coefficient of V _{oc}	-0.24%/°C
Temperature Coefficient of I _{sc}	+0.046%/°C


Operating parameters

Operating Temperature	-40°C~+70°C
Module [T ₉₈] max	70°C
Maximum System Voltage	1500V DC
Maximum Series Fuse Rating	30A
Power Selection Tolerance	0~+3%
Bifaciality coefficient of P _{max}	80±10%
Bifaciality coefficient of V _{oc}	98±5%
Bifaciality coefficient of I _{sc}	80±10%
Fire Class Rating	Class C


Mechanical parameters

Cell Type	TNC (N Type Monocrystalline Cell)
Cell Orientation	96[6×16]
Dimensions	1762±2×1134±2×30mm
Weight	22.8kg
Front Glass	2.0mm AR coating semi tempered glass
Rear Glass	2.0mm semi tempered glass
Frame	Anodized aluminum alloy black frame
Junction Box	IP68, 3diodes
Cable	4.0mm ²
Cable length	+1200mm, -1200mm, length can be customized
Connector	TW-PVCON-01(Tongwei Solar) PV-KST4-EVO2/xy_UR, PV-KBT4-EVO2/xy_UR(Staubli) PV-KST4-EVO2A/xy, PV-KBT4-EVO2A/xy(Staubli) PV-ZH202B(Zhejiang Zhonghuan Sunter)
Max static test load	Front side 5400Pa, Rear side 2400Pa
Per pallet	36pcs
Packaging	936pcs per 40'HC

Warranty



I-V Curve



Certifications

Quality Management System and Product Certification

ISO 9001: 2015 / Quality management systems
ISO 14001: 2015 / Environmental management systems
ISO 45001: 2018 / Occupational health and safety management systems
ISO 50001: 2018 / Energy management systems
IEC 62941: 2019 / Quality system for PV module manufacturing
IEC 61215(2021) / IEC 61730(2023)



Email: sales@tongwei.com Website: <https://en.tongwei.cn/> Add: No.588, Middle Section Tianfu Avenue, High-Tech Zone, Chengdu, China (Sichuan) Pilot Free Trade Zone Tel: +86-028-60707985

Statement: With technological process and product update, there may be deviation between the technical parameters of Tongwei's module products and the technical parameters contained in the specification, and Tongwei Solar has the right to adjust the technical parameters at any time without notifying the customer, the final interpretation of the technical specification is vested in Tongwei Solar. (TP Glass-AU-20250523) Made in China



TWMNH

N-type Half-cell Dual Glass
Monofacial Full-black Module(48)

48HE440-470W

High Power Output
Low LCOE



Maximum Power
470W




TIER 1
Bloomberg
NEW ENERGY FINANCE



Tongwei Co.,Ltd.
<https://en.tongwei.cn/>



Learn More

 Drawing (Unit: mm) Electrical Characteristics (STC)

Module type:	TWMNH-48 HE440	TWMNH-48 HE445	TWMNH-48 HE450	TWMNH-48 HE455	TWMNH-48 HE460
Maximum Power: P _{max} [W]	440	445	450	455	460
Open Circuit Voltage: V _{oc} [V]	35.65	35.80	35.95	36.10	36.25
Short Circuit Current: I _{sc} [A]	15.74	15.79	15.84	15.89	15.94
Voltage at Maximum Power: V _{mp} [V]	29.55	29.85	30.15	30.44	30.73
Current at Maximum Power: I _{mp} [A]	14.89	14.91	14.93	14.95	14.97
Module Efficiency: η [%]	22.0	22.3	22.5	22.8	23.0

* STC: Irradiance 1000W/m², Cell Temperature 25°C, AM=1.5, Power measurement tolerance ±3%

 Temperature Rating



Temperature Coefficient of P _{max}	-0.28%/°C
Temperature Coefficient of V _{oc}	-0.24%/°C
Temperature Coefficient of I _{sc}	+0.046%/°C

 Operating Parameters

Operating Temperature	-40°C~+70°C
Module [T ₉₈] max	70°C
Maximum System Voltage	1500V DC
Maximum Series Fuse Rating	30A
Power Selection Tolerance	0~+3%
Fire Class Rating	Class C

 Mechanical Parameters


Cell Type	TNC (N Type Monocrystalline Cell)
Cell Orientation	96[6×16]
Dimensions	1762±2×1134±2×30mm
Weight	22.8kg
Front Glass	2.0mm AR coating semi tempered glass
Rear Glass	2.0mm semi tempered glass
Frame	Anodized aluminum alloy black frame
Junction Box	IP68, 3diodes
Cable	4.0mm ²
Cable length	+1200mm, -1200mm, length can be customized
Connector	TW-PVCON-01(Tongwei Solar) PV-KST4-EVO2/xy_UR, PV-KBT4-EVO2/xy_UR(Staubli) PV-KST4-EVO2A/xy, PV-KBT4-EVO2A/xy(Staubli) PV-ZH202B(Zhejiang Zhonghuan Sunter)
Max static test load	Front side 5400Pa, Rear side 2400Pa
Per pallet	36pcs
Packaging	936pcs per 40'HC

 Linear Warranty I-V Curve Certifications

Quality Management System and Product Certification

ISO 9001: 2015 / Quality management systems
ISO 14001: 2015 / Environmental management systems
ISO 45001: 2018 / Occupational health and safety management systems
ISO 50001: 2018 / Energy management systems
IEC 62941: 2019 / Quality system for PV module manufacturing
IEC 61215(2021) / IEC 61730(2023)



 Drawing (Unit: mm) Electrical Characteristics (STC)

Module type:	TWMNH-48 HE465	TWMNH-48 HE470
Maximum Power: P _{max} [W]	465	470
Open Circuit Voltage: V _{oc} [V]	36.40	36.55
Short Circuit Current: I _{sc} [A]	15.99	16.00
Voltage at Maximum Power: V _{mp} [V]	31.03	31.34
Current at Maximum Power: I _{mp} [A]	14.99	15.00
Module Efficiency: η [%]	23.3	23.5

* STC: Irradiance 1000W/m², Cell Temperature 25°C, AM=1.5, Power measurement tolerance: ±3%

 Temperature Rating



Temperature Coefficient of P _{max}	-0.28%/°C
Temperature Coefficient of V _{oc}	-0.24%/°C
Temperature Coefficient of I _{sc}	+0.046%/°C

 Operating Parameters

Operating Temperature	-40°C~+70°C
Module [T ₉₈] max	70°C
Maximum System Voltage	1500V DC
Maximum Series Fuse Rating	30A
Power Selection Tolerance	0~+3%
Fire Class Rating	Class C

 Mechanical Parameters

Cell Type	TNC (N Type Monocrystalline Cell)
Cell Orientation	96[6×16]
Dimensions	1762±2×1134±2×30mm
Weight	22.8kg
Front Glass	2.0mm AR coating semi tempered glass
Rear Glass	2.0mm semi tempered glass
Frame	Anodized aluminum alloy black frame
Junction Box	IP68, 3diodes
Cable	4.0mm ²
Cable length	+1200mm, -1200mm, length can be customized
Connector	TW-PVCON-01(Tongwei Solar) PV-KST4-EVO2/xy_UR, PV-KBT4-EVO2/xy_UR(Staubli) PV-KST4-EVO2A/xy, PV-KBT4-EVO2A/xy(Staubli) PV-ZH202B(Zhejiang Zhonghuan Sunter)
Max static test load	Front side 5400Pa, Rear side 2400Pa
Per pallet	36pcs
Packaging	936pcs per 40'HC

 Linear Warranty I-V Curve Certifications

Quality Management System and Product Certification

ISO 9001: 2015 / Quality management systems
ISO 14001: 2015 / Environmental management systems
ISO 45001: 2018 / Occupational health and safety management systems
ISO 50001: 2018 / Energy management systems
IEC 62941: 2019 / Quality system for PV module manufacturing
IEC 61215(2021) / IEC 61730(2023)





TWMNH

N-type Half-cell Dual Glass
Monofacial Black Frame Module(48)

48HW440-475W

High Power Output
Low LCOE



Maximum Power
475W




Tongwei Co.,Ltd.
<https://en.tongwei.cn/>



Learn More

Drawing (Unit: mm)



Electrical Characteristics (STC)

Module type:	TWMNH-48 HW440	TWMNH-48 HW445	TWMNH-48 HW450	TWMNH-48 HW455	TWMNH-48 HW460
Maximum Power: P _{max} [W]	440	445	450	455	460
Open Circuit Voltage: V _{oc} [V]	35.65	35.80	35.95	36.10	36.25
Short Circuit Current: I _{sc} [A]	15.74	15.79	15.84	15.89	15.94
Voltage at Maximum Power: V _{mp} [V]	29.55	29.85	30.15	30.44	30.73
Current at Maximum Power: I _{mp} [A]	14.89	14.91	14.93	14.95	14.97
Module Efficiency: η [%]	22.0	22.3	22.5	22.8	23.0

* STC: Irradiance 1000W/m², Cell Temperature 25°C, AM=1.5, Power measurement tolerance ±3%

Temperature Rating

Temperature Coefficient of P _{max}	-0.28%/°C
Temperature Coefficient of V _{oc}	-0.24%/°C
Temperature Coefficient of I _{sc}	+0.046%/°C


Operating Parameters

Operating Temperature	-40°C~+70°C
Module [T98] max	70°C
Maximum System Voltage	1500V DC
Maximum Series Fuse Rating	30A
Power Selection Tolerance	0~+3%
Fire Class Rating	Class C


Mechanical Parameters

Cell Type	TNC (N Type Monocrystalline Cell)
Cell Orientation	96[6×16]
Dimensions	1762±2×1134±2×30mm
Weight	22.8kg
Front Glass	2.0mm AR coating semi tempered glass
Rear Glass	2.0mm semi tempered glass
Frame	Anodized aluminum alloy black frame
Junction Box	IP68, 3diodes
Cable	4.0mm ²
Cable length	+1200mm, -1200mm, length can be customized
Connector	TW-PVCON-01(Tongwei Solar) PV-KST4-EVO2/xy_UR, PV-KBT4-EVO2/xy_UR(Staubli) PV-KST4-EVO2A/xy, PV-KBT4-EVO2A/xy(Staubli) PV-ZH202B(Zhejiang Zhonghuan Sunter)
Max static test load	Front side 5400Pa, Rear side 2400Pa
Per pallet	36pcs
Packaging	936pcs per 40' HC

Linear Warranty



I-V Curve




Certifications

Quality Management System and Product Certification

ISO 9001: 2015 / Quality management systems
ISO 14001: 2015 / Environmental management systems
ISO 45001: 2018 / Occupational health and safety management systems
ISO 50001: 2018 / Energy management systems
IEC 62941: 2019 / Quality system for PV module manufacturing
IEC 61215(2021) / IEC 61730(2023)



 Drawing (Unit: mm) Electrical Characteristics (STC)

Module type:	TWMNH-48 HW465	TWMNH-48 HW470	TWMNH-48 HW475
Maximum Power: P _{max} [W]	465	470	475
Open Circuit Voltage: V _{oc} [V]	36.40	36.55	36.70
Short Circuit Current: I _{sc} [A]	15.99	16.00	16.01
Voltage at Maximum Power: V _{mp} [V]	31.03	31.34	31.65
Current at Maximum Power: I _{mp} [A]	14.99	15.00	15.01
Module Efficiency: η [%]	23.3	23.5	23.8

* STC Irradiance 1000W/m², Cell Temperature 25°C, AM=1.5, Power measurement tolerance: ±3%

 Temperature Rating



Temperature Coefficient of P _{max}	-0.28%/°C
Temperature Coefficient of V _{oc}	-0.24%/°C
Temperature Coefficient of I _{sc}	+0.046%/°C

 Operating Parameters

Operating Temperature	-40°C~+70°C
Module [T ₉₈] max	70°C
Maximum System Voltage	1500V DC
Maximum Series Fuse Rating	30A
Power Selection Tolerance	0~+3%
Fire Class Rating	Class C

 Mechanical Parameters

Cell Type	TNC (N Type Monocrystalline Cell)
Cell Orientation	96[6×16]
Dimensions	1762±2×1134±2×30mm
Weight	22.8kg
Front Glass	2.0mm AR coating semi tempered glass
Rear Glass	2.0mm semi tempered glass
Frame	Anodized aluminum alloy black frame
Junction Box	IP68, 3diodes
Cable	4.0mm ²
Cable length	+1200mm, -1200mm, length can be customized
Connector	TW-PVCON-01(Tongwei Solar) PV-KST4-EVO2/xy_UR, PV-KBT4-EVO2/xy_UR(Staubli) PV-KST4-EVO2A/xy, PV-KBT4-EVO2A/xy(Staubli) PV-ZH202B(Zhejiang Zhonghuan Sunter)
Max static test load	Front side 5400Pa, Rear side 2400Pa
Per pallet	36pcs
Packaging	936pcs per 40'HC

 Linear Warranty I-V Curve Certifications

Quality Management System and Product Certification

ISO 9001: 2015 / Quality management systems
ISO 14001: 2015 / Environmental management systems
ISO 45001: 2018 / Occupational health and safety management systems
ISO 50001: 2018 / Energy management systems
IEC 62941: 2019 / Quality system for PV module manufacturing
IEC 61215(2021) / IEC 61730(2023)

